



Wonnemann - Natural wood edge banding

A beautiful profile, however you look at it!

At Wonnemann, the careful selection of veneers, the instinct of our staff and state of the art technology all guarantee the excellent quality of our genuine wood edgings. Our selection of edgings is huge:

- ▶ Veneer edge banding
- ▶ Veneer edge banding **HotCoating®**
- ▶ Thick veneer edge banding
- ▶ Thick edge banding with transverse veneer

No matter how thick or thin – genuine wood edge banding are typically produced and coated on a roll, thereby enabling immediate application in the user's production process.

HotCoating® veneer edge banding

As an alternative to coated edgings, Wonnemann produces genuine wood edge banding with a new and innovative seal: a PUR coat designated **HotCoating®**.


This innovation by KLEIBERIT® achieves excellent surface hardness (100% solid matter) by chemically wetting the veneer edging. The result is an impressive resilience to impact, abrasion and scratching. What particularly sets this UV-stable PUR edging apart from other coating systems is its high degree of flexibility - definitely recommended for the tightest sheathing radii! **HotCoating®** veneer edging is used, for example, as sheathing material in the window and door manufacturing industries.

Thick edge banding with transverse veneer

Thick edge banding with transverse veneers are created by adhesion bonding of at least 2 layers of veneer. The veneer substrate is glued longitudinal and the face veneer transversely in a special PUR process. This results in a technical rigidity that allows for processing of tough edgings with transverse veneers from the roll.

Transverse wood grain gives furniture a striking design. Wonnemann tough edgings with transverse grain emphasise this impressive look. One thing is for sure: **Workpieces with transverse veneer are trendy – so are Wonnemann's tough edgings with transverse veneer!**

Thanks to our versatile options for natural wood edging production, Wonnemann can easily fulfil your edging requirements.



The mark of responsible forestry

Specifications ▶ ▶ ▶



Gerhard Wonnemann Holzwerk GmbH · Mühlenstraße 16 · 33378 Rheda-WIEDENBRÜCK / Germany
 Fon: +49(0)5242 160 · Fax: +49(0)5242 16-72 · info@wonnemann-holzwerk.de · www.wonnemann-holzwerk.de