



Wonnemann - Profile plywood

Expand your profile with this plywood!

The elegant plywood panels from Wonnemann are produced from carefully selected sliced and peeled veneers. The best veneer qualities in the upper layers ensure versatile processing options. This enables the production of panels which can be used for **individual profiles** or as **profile plywood**.

The milling of profile plywood is usually conducted in accordance with the direction of the veneer. You can choose between the veneer and profiling run:

- ▶ vertical,
- ▶ right-,
- ▶ left-diagonal,
- ▶ fishbone or
- ▶ diamond.

In a normal groove depth of 4.5 mm the veneer of the base of the groove is colour-coordinated to the respective top veneer. Naturally we take this colour harmony into account for all panel thicknesses and individual groove depths. The waterproof bonding AWW corresponds to the standards specified by the quality association Sperrholz e.V. and is subject to periodic examination: **Therefore high quality is guaranteed!**

Special finishes can be applied to the surface by using a base coat, customary glazes and lacquers. This provides the finishing touch to the beautiful appearance of the plywood.


The close inserts, good distortion characteristics (compared to solid wooden panels) and the decorative character mean that Wonnemann-profile plywood panels are particularly suitable for:

- ▶ individual design of entrance door panels,
- ▶ cross lamination to composite elements or entrance door blanks,
- ▶ bases for entrance door panels,
- ▶ garage door panels,
- ▶ wall and ceiling panelling.

Profile plywood - naturally beautiful!

For all those who wish to give their homes a special appearance!

Take advantage of our know-how, our technical expertise and the variety of our panels. We are able to implement solutions for many types of application.




Qualitätsgemeinschaft
Sperrholz e.V.

Specifications ▶ ▶ ▶



WONNEMANN
H O L Z W E R K

Gerhard Wonnemann Holzwerk GmbH · Mühlenstraße 16 · 33378 Rheda-WIEDENBRÜCK / Germany
Fon: +49(0)5242 160 · Fax: +49(0)5242 16-72 · info@wonnemann-holzwerk.de · www.wonnemann-holzwerk.de



Specifications

Wonnemann - Profile plywood

- Version A:** **Fancy veneered plywood for profiling**
smooth, suitable for a groove depth of 4.5 mm
- Version B:** **Profile plywood**
groove depth 4.5 mm, ridge width 85 mm, rounded groove flanks
- Top veneers:** selected sliced and peeled veneers
- Wood types:** Okoumé sliced and peeled veneer, Okoumé Finition, Carolina Pine, Moabi, Calabrian Pine, Spruce, Oak, Sapele, Khaya
- Veneer run:** vertical, right / left-diagonal, fishbone, diamond
- Inserts:** high-quality peeled veneer, longitudinal groove base that is colour-coordinated to match the top veneer
- Thicknesses:** standard 9.5 mm
- Layers:** 5-ply
- Panel sizes:** 2500 x 1700 mm 2150 x 920 mm
2500 x 1250 mm 2250 x 1100 mm
- Bonding:** AW according to DIN 68705
- Special features:** other wood types and thicknesses, such as 12 mm, 15 mm and 17 mm with individual groove depths, are available on request.

**Available
from stock.**

**For more
information,
see our
price list.**

© Gerhard Wonnemann Holzwerk GmbH

In order to be able to address your individual needs please provide us with details of the intended use, dimensions, your requirements and quality criteria. We would be pleased to implement your requests.

We promise you top quality!

